

# Gödde

Maschinenbau GmbH

## Tool turning devices.



## Our tools for your vehicles.

- Increased flexibility in excavator operation
- Increases economic efficiency
- Quick turning of the working tool from the driver's platform
- Stops for limiting rotation possible
- No oil feed-through
- Sealed version
- Smooth device connection plate for the implement underneath the tool turning device
- Above connection option for corresponding mounting plate to the carrier vehicle



- Driven by hydraulic motor



- With customization on request to the working tool

- Can be combined with our flail and forestry mulchers
- Various excavator mounts including hose package available



# You will do well with us.



| Technical data.                              | Abbr.   | WDS 05 | WDS 10 | WDS 20 |
|--|---------|--------|--------|--------|
| Carrier vehicle up to.<br>(operating weight) | t       | 5      | 10     | 20     |
| Swivel range.<br>(for WDS 05.10 with stops)  | degree  | 200    | 200    | 270    |
| Weight slewing ring.                         | kg      | 80     | 100    | 135    |
| Weight with holder approx.                   | kg      | 100    | 300    | 500    |
| Height without mount.                        | mm      | 100    | 190    | 260    |
| Length.                                      | mm      | 400    | 450    | 660    |
| Width.                                       | mm      | 350    | 550    | 600    |
| Oil quantity.                                | l/min   | 35     | 35     | 50     |
| Oil pressure.                                | bar     | 120    | 120    | 250    |
| Torque.                                      | Nm max. | 10.000 | 15.000 | 24.200 |

Gödde Maschinenbau GmbH - Diekstraße 59 - 49809 Lingen  
 Phone +49 (0) 591-97307-21  
 Fax. +49 (0) 591-97307-58  
 E-mail. a.hilling@goedde-lingen.de  
 Web. www.goedde-lingen.de

